



Laykold[®]
MASTERS

Sealer

1. General Description

Laykold Masters Sealer is a one component, thixotropic, latex emulsion sealer. Laykold Masters Sealer is environmentally friendly containing no asbestos, Lead, or Mercury.

Basic Use: Laykold Masters Sealer is designed to seal porous SBR mats prior to the application of water-based coatings.

2. Safety Guidelines

Always wear the recommended personal protective equipment. Avoid contact with eyes, skin, and clothing. Adequate ventilation is required during application. CAUTION: eye and respiratory irritant (ammonia).

3. Storage and Packaging

Laykold Masters Sealer should be kept dry, cool, and in original packaging.

Packaging: 5 gallon pail at 20.82 kg

4. Coverage

Laykold Masters Sealer coverage is approximately 0.15-0.20 kg/m² (0.04-0.05 gal/yd² or 180-225 ft²/gal) per application of undiluted material.

5. Installation Guidelines

The surface must be clean, dry, and free of oil, grease, dirt, and any foreign residue.

Laykold Masters Sealer is ready to use and should be applied with a flat trowel. Laykold Masters Sealer is applied in 2 coats. The 2nd coat should be applied at a 90° angle to the 1st coat. Due to the ammonia content in the Laykold Masters Sealer, a full face respiratory with

Features and Benefits

- ✓ Thixotropic
- ✓ Easy application
- ✓ Does not contain asbestos, Lead, or Mercury
- ✓ Excellent sealer



6. Limitations

- Minimum surface and application temperature: 10°C (50°F)
- Maximum surface and application temperature: 54°C (130°F)
- Do not apply when rain is imminent
- Do not allow to freeze
- Do not over dilute with water
- Dry time: 2-4 hours, dependent upon weather conditions
- Sealed surfaces should be coated within 24 hours

7. Technical Data

Results based on temperature of 23°C (73°F) and 50% Humidity

Density	1.05-1.15 g/cm ³
Viscosity	Thixotropic
Color	White
Tack Free Time	2-4 hours

*Based on standard formula calculation

Above figures are guide values and should not be used as a base for specifications

Consult the Safety Data Sheet (SDS) for more details

For complete and latest warranty and product information, please visit www.advpolytech.com

