

LONG-TERM PROTECTIVE FLOOR COATING FOR *CONCRETE AND ASPHALT SUBSTRATES*



APT – an ISO 9001 & 14001
certified company

Qualifloor®



- ✓ Fast-Curing Primerless Product
- ✓ Easy Cleaning—One Single, High Gloss Coating
- ✓ Excellent UV Resistance—Stays The Same Color, No Loss of Physical Properties
- ✓ Options Available: Clear/Pigmented, Can Be Used Alone or With Flake/Paint Chips or Colored Sand
- ✓ Meets All National Regulations for VOC—Low VOC (12 g/L)
- ✓ Low Odor and Shortened Downtime
- ✓ High Abrasion Resistance (CM 17, 1000 cycles), Taber Abrasion of 16.2—Longevity
- ✓ Chemical Resistant—Acetone, Methenol, Standard Chemicals
- ✓ Elongation of 5%, High Tensile Strength 48 N/mm²—More Force to Rip, Will Not Break

Test Method	Test	Result
ASTM D412	Elongation	5%
ASTM D 412	Tensile Strength	8,000 psi
ASTM D2240	Hardness	70 D Scale
ASTM D4060	Abrasion Resistance (CM 17)	16.2 mg loss



APT AMERICAS

World Headquarters
109 Conica Lane,
PO Box 160
Harmony, PA 16037 USA
Tel. (724) 452-1330
Fax. (724) 452-1703

APT ASIA PACIFIC

Factory 3 Dunlopillo Drive
Dandenong Victoria 3175 Australia
Tel. +61 3 8792 8000
Fax. +61 3 8792 8001